

MATERIAL SAFETY DATA SHEET



NPC 100

* FOR CHEMICAL EMERGENCY *
* Spill, Leak, Fire, Exposure, or Accident *
* CALL CHEMTREC -- DAY OR NIGHT 800-424-9300 *

***** SECTION 1 -- PRODUCT INFORMATION *****

Manufacturer's name.....: EVEREST COATINGS
Manufacturer's telephone No.: (281) 350-9800
Product name.....: **Non-Plasticizing Caulk NPC 100**
Manufacturer's code number..: 709
Chemical formula: Complex mixture - Acrylic Sealant
C.A.S. Number: N/A E.P.A. Number: N/A
Date Prepared: 7/12/95 Date Revised:
HMIS RATING
Health hazard 1
Flammability hazard 0
Reactivity hazard 0

***** SECTION II -- INGREDIENTS *****

COMPONENT	CAS NO.	%	LD50
Proprietary mixture			
Calcium Carbonate	7732-18-5	20-30	Orl Rat 6,540
Hydrocarbon Resins	N/A	>3	N/E
Chlorinated Paraffin	61788-76-9	>3	N/E
Hydrated Alumina	21645-51-2	>3	N/E
Water	7732-18-5	<40	N/E

***** SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS *****

Appearance: Liquid Color: White or colored Odor: Ammonia
Solubility: Water reducible Boiling Pt: 212°F Melt Pt: <32°F
Specific Gravity: >1.3 Vapor Density: <Air % Volatile: <40
Evaporation Rate (Ether = 1): <1

***** SECTION IV -- FIRE AND EXPLOSION HAZARD DATA *****

Flash Point : Non-combustible Flammable limits (LFL/UFL) N/A
EXTINGUISHING MEDIA: Not applicable
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH-approved or equivalent and full protective gear.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Material can splatter above 100°C/212°F. Polymer film can burn.

MATERIAL SAFETY DATA SHEET

***** SECTION V -- REACTIVITY DATA *****

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID): Not applicable